



RUSTIC STAIN
Solid Color Oil
3551 LINE

SECTION NO. 11 ADS 1202

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
Alkyd	Flat	125 - 300 Sq Ft Per Gallon	Brush, Roller, Pad or Spray	Mineral Spirits	Mineral Spirits	4-6 Hours	12 Hours	10 Days
PRODUCT NAME: 3551 Line Rustic Stain Solid Color Oil		Solid Color Oil Stain is richly pigmented to provide an opaque appearance without obscuring the beauty and texture of wood.						
WHERE TO USE:		Exterior Wood: On exterior vertical surfaces, such as wood siding, shakes, fences, or beams. Not recommended for horizontal surfaces or decks.						
Surface Preparation:		Surface to be painted must be clean and free of dirt, chalk, wax, grease, rust or loose, flaking paint. Dirt and chalk should be removed by power washing or hand scrubbing with T.S.P. (or equivalent) and water, followed by a clean water rinse. Wax should be removed by solvent cleaning. Grease should be cleaned by using Coronado Sur-Prep. Feather sand rough edges to insure a smooth finish coat. Prior to painting any mildewed surface, thoroughly remove the mildew by scrubbing with a strong solution of powdered cleanser (or T.S.P.) and warm water with 8 oz. of household bleach added per gallon. Rinse thoroughly and allow to dry completely before painting. Apply directly to bare wood, as this stain is self-priming.						
Application:		Stir the product thoroughly prior to use and periodically during application. Solid Color Oil Stain may be applied by brush, roller, pad or spray. Spray application on weathered surfaces should be back brushed to work stain into the wood. To insure uniform color and wood grain prominence, flow stain on with a full applicator following the grain pattern. Always maintain a wet edge to paint into. The spreading capacity of Solid Color Oil Stain is 125 to 300 sq ft per gallon, one coat, depending on surface texture and porosity. No thinning is recommended for this product. Avoid painting over hot surfaces or in direct sunlight. Apply only when surface and air temperatures are above 50°F. Do not apply if rain is threatening.						
NOTE: Formulated without mercury or lead.								

Resin Type:	Alkyd
Solids:	Weight – 55.4% Volume – 37.0%
Weight Per Gallon:	9.40 lbs.
Viscosity:	63 – 66 (Krebs Units)
Specular Gloss:	1 – 2% @ 85 Degrees
Recommended Film Thickness:	Wet – 3.5 to 4.0 mils Dry – 1.3 to 1.5 mils
VOC / VOS Statement:	This product contains less than 2.92 lbs. or 350 GPL per gallon.
Cautions:	<p>CAUTION ! COMBUSTIBLE Contains Mineral Spirits Keep away from heat & flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Close container after each use. Avoid contact with skin. Use with adequate ventilation. NOTICE: Reports have associated repeated and prolonged occupational over-exposure to solvents with permanent brain & nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.</p> <p>KEEP OUT OF REACH OF CHILDREN.</p>