

M A T E R I A L S A F E T Y D A T A S H E E T

1050 TINTABLE WHITE

Page: 1

PRODUCT NAME: 1050 TINTABLE WHITE
PRODUCT CODE: 1050

HMIS CODES: H F R P
1 0 0 B

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: O'Leary Paint Company
ADDRESS : 415 Baker Street
PMI Division
Lansing, MI. 48910

EMERGENCY PHONE : DATE PRINTED : 11/28/01
INFORMATION PHONE : (517) 487-2033 NAME OF PREPARER : SCOTT BOWER

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

| WEIGHT REPORTABLE COMPONENTS PERCENT | CAS NUMBER | mm Hg | TEMP | VAPOR PRESSURE |
|--|------------|-------|------|----------------|
| ETHYLENE GLYCOL | 107-21-1 | .1 | 68 | 0 |
| OSHA PEL: 50 ppm, ACGIH TLV: 100 mg/m3 | | | | |

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***
N/A

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 387 deg F SPECIFIC GRAVITY (H2O=1): 1.28
VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C.: 0.85 lb/gl MATERIAL V.O.C.: 0.25 lb/gl
SOLUBILITY IN WATER: INFINITE
APPEARANCE AND ODOR: WHITE OPAQUE LIQUID & SLIGHTLY SWEET ODOR.

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: 232 deg F METHOD USED: TCC
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 3.2 UPPER: 15.3

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES
SUMMON PROFESSIONAL FIREFIGHTERS. USE FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WATER SHOULD BE USED TO COOL CONTAINERS.

UNUSUAL FIRE AND EXPLOSION HAZARDS
DUE TO PRESSURE BUILD-UP, CLOSED CONTAINERS EXPOSED TO EXTREME HEAT MAY EXPLODE. DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION.

===== SECTION V - REACTIVITY DATA =====

M A T E R I A L S A F E T Y D A T A S H E E T

1050 TINTABLE WHITE

Page: 2

STABILITY: STABLE
CONDITIONS TO AVOID
KEEP FROM FREEZING.

INCOMPATIBILITY (MATERIALS TO AVOID)
N/A

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
MAY CAUSE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION.

HAZARDOUS POLYMERIZATION: WILL OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
MAY CAUSE IRRITATION OF THE RESPIRATORY TRACT; HEADACHES, NAUSEA, DIZZINESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE
MAY CAUSE SKIN AND EYE IRRITATION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
DRYNESS, ITCHING, CRACKING, BURNING, REDNESS, AND SWELLING ARE ASSOCIATED WITH
EXCESSIVE SKIN CONTACT.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA.

HEALTH HAZARDS (ACUTE AND CHRONIC)
THIS PRODUCT CONTAINS ETHYLENE GLYCOL. OVEREXPOSURE TO THIS MATERIAL HAS BEEN
SUGGESTED AS A CAUSE OF THE FOLLOWING EFFECTS IN HUMANS; LIVER ABNORMALITIES,
KIDNEY DAMAGE,CENTRAL NERVOUS SYSTEM EFFECTS.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No
N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE
N/A

EMERGENCY AND FIRST AID PROCEDURES
INHALATION:REMOVE TO FRESH AIR. EYES:IN CASE OF EYE CONTACT, FLUSH WITH LARGE
AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SKIN:REMOVE WITH SOAP AND WATER,
REMOVE SOILED CLOTHING. INGESTION:DRINK 1 OR 2 GLASSES OF WATER TO DILUTE.DO NOT
INDUCE VOMITING. CONSULT PHYSICIAN IMMEDIATELY. HAVE MATERIAL SAFETY DATA SHEET
INFORMATION AVAILABLE.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
PROVIDE MAXIMUM VENTILATION. REMOVE ALL SOURCES OF IGNITION.TAKE UP SPILLED
MATERIAL WITH SAWDUST,VERMICULITE, OR OTHER ABSORBENT MATERIAL AND PLACE INTO
CONTAINERS FOR PROPER DISPOSAL. WASH WITH WATER.

M A T E R I A L S A F E T Y D A T A S H E E T

1050 TINTABLE WHITE

Page: 3

WASTE DISPOSAL METHOD

WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY CONTAINERS SHOULD BE RECYCLED OR DISPOSED OF THROUGH AN APPROVED MANAGEMENT FACILITY.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

STORE BELOW 110F. KEEP FROM FREEZING. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

OTHER PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

DO NOT BREATHE SPRAY MIST, OR SANDING DUST. WHEN USED IN RESTRICTED VENTILATION AREAS, WEAR NIOSH/MSHA APPROVED AIR SUPPLY RESPIRATOR OR HOOD.

VENTILATION

USE WITH ADEQUATE VENTILATION. PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAMINANT CONCENTRATION BELOW CURRENT APPLICABLE SAFETY STANDARDS IN APPLICATION AND CURING AREAS.

PROTECTIVE GLOVES

GLOVES CONSTRUCTED OF: POLYVINYL ALCOHOL, NEOPRENE RUBBER, OR LATEX RUBBER.

EYE PROTECTION

DO NOT GET IN EYES. SAFETY EYE WEAR WITH SPLASH GUARDS OR SIDESHIELD IS RECOMMENDED TO PREVENT CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NOT REQUIRED.

WORK/HYGIENIC PRACTICES

REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING THE WASHROOM.

===== SECTION IX - DISCLAIMER =====

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED BY O'LEARY PAINT CO. TO BE ACCURATE, BUT WE DO NOT ASSUME ANY LIABILITY FOR THE ACCURACY OF THIS INFORMATION. WE NEITHER SUGGEST NOR GUARANTEE THAT ANY HAZARDS MENTIONED ARE THE ONLY ONES WHICH EXIST.