



**ProWise
Interior/Exterior
Block Filler
126 Line**

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
Acrylic Latex	Flat	Up to 50-100 Sq Ft Per Gallon	Brush, Roller, Or Airless Spray	Clean Water	Warm Soapy Water	1 Hour	4 Hours	7 Days
PRODUCT NAME: 126 Line ProWise Interior/Exterior Block Filler		This Latex Block Filler is formulated with heavy pigmentation and high viscosity to fill the pores in concrete block (CMU) surfaces prior to application of the finish coat.						
WHERE TO USE:		Cement Concrete Masonry Blocks	On interior or exterior above grade cementitious substrates where a smooth, uniform surface is desired. New cementitious substrates should cure at least 30 days; the pH must be 11.0 or lower prior to application.					
SURFACE PREPARATION:		Surfaces to be filled must be clean, dry, dull and free from oil, grease, form release agents and water soluble materials. Remove all loose mortar scale, efflorescence, dust or mildew. Patch holes, cracks and other surface imperfections with acrylic caulk or a masonry patch; allow to dry thoroughly.						
APPLICATION:		<p>Stir product with a circular lifting motion. This block filler may be brushed, rolled or sprayed and back-rolled with an airless sprayer. The spray and back-roll method is by far the most efficient application method. Apply generously as it comes from the container working the material into the substrate to fill all voids. Use a ½ to 1-1/2 gpm airless with a .021 - .035 tip for spray and back-roll application. Do not apply when surface or air temperatures are below 50°F. DO NOT THIN. A second coat may be applied if required to achieve a pin-hole free surface.</p> <p>THIS PRODUCT MUST BE TOPCOATED ON EXTERIOR APPLICATIONS.</p> <p>NOT FOR USE IN CONTINUOUSLY WET OR DAMP INTERIOR AREAS</p>						
NOTE: Formulated without mercury or lead.								

RESIN TYPE:	Vinyl Acrylic / Acrylic
SOLIDS:	Weight – 61.0% Volume – 41.3%
WEIGHT PER GALLON:	12.5 lbs.
VISCOSITY:	122-128 (Krebs Units)
FLASH POINT:	200° F or over (TT-P-141, Method 4293)
SPECULAR GLOSS:	0 – 5% @ 85 Degrees
SAG RATING:	Pass 26 mils (Lenetta)
LIGHT REFLECTANCE:	N / A
RECOMMENDED FILM THICKNESS:	Wet – 16.0 – 20.0 Mils Dry – 8.4 – 10.5 Mils
VOC – VOS STATEMENT:	This product contains 26 grams per liter.
<p style="text-align: center;">CAUTION!</p> <p>Do not take internally. Close container after each use.</p> <p style="text-align: center;">KEEP FROM FREEZING.</p> <p style="text-align: center;">KEEP OUT OF REACH OF CHILDREN.</p>	<p style="text-align: center;">WISE PAINT CO.</p> <p style="text-align: center;">415 Baker St Lansing, MI 48910 www.wisepaints.com</p>

04/15/2016

