



**CeramicWise  
Matte  
LOW ODOR  
STAIN RESISTANT  
140 LINE**

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
100% Acrylic	Matte	350 to 400 Sq Ft Per Gallon	Brush, Roller, Pad or Airless Spray	Clean Water	Warm Soapy Water	30 Minutes	4 Hours	30 Days
<b>PRODUCT NAME:</b> CeramicWise Matte		A top grade interior, 100% acrylic, low odor, matte wall paint, formulated with ceramic spheres to impart excellent stain resistance properties. Finger prints, soil, grease, and many other stains wash off with mild soap and water without harming the film.						
<b>WHERE TO USE:</b>		Drywall Plaster Wood Metal Masonry  This matte latex wall paint is a very low odor, low VOC product, making it perfect for hospitals, schools, homes or any area where odor is a concern. It allows a flat finish in high use areas, with maximum durability.						
<b>Surface Preparation:</b>		<p><b>New Work:</b> The surface to be coated must be clean and free of dust, grease, wax, rust, oil, and bleeding stains.</p> <p><b>Priming:</b>            Drywall / Plaster – Prime with 145 CeramicWise Primer or this product.            Wood – Prime with 145 CeramicWise Primer.            Ferrous Metal – Rust inhibiting metal primer such as #35-11, #2090 or #925-147.            Non-Ferrous Metal – Dull new non-ferrous metal with a maroon scrub pad and prime with 145 CeramicWise Primer.            Masonry – Prime with poured or precast masonry with 145 CeramicWise Primer. Fill porous block 136 TechWise Acrylic Block Filler or 126 ProWise Latex Block Filler.</p> <p><b>Repaint Work:</b> Remove any oil, chalk, dirt, wax or dust prior to re-coating. Any loose or flaking paint should be removed, patched and the edges feather sanded to produce a smooth, uniform surface. Dull glossy surfaces to insure good adhesion. On previously painted surfaces in good repair, no priming is generally necessary. Spot prime bare areas with this product or the primer indicated above.</p>						
<b>Application:</b>		Stir product with a circular, lifting motion to disperse into a homogenous liquid. To achieve proper results a quality 3/8" nap roller cover is required when using products containing ceramic microspheres. Brush – Nylon or polyester filament. Airless Spray – Tip at atomization pressures will vary with type of equipment, viscosity and temperature. An orifice of .017 - .019 will provide the most satisfactory spray pattern. Best results are more likely obtained by using quality application tools. Do not apply directly over chalky surfaces or bleeding stains.						
<b>NOTE: Formulated without mercury or lead.</b>								

<b>Resin:</b>	100% Acrylic
<b>Solids:</b>	Volume – 37.5
<b>Weight Per Gallon:</b>	10.85 lbs.
<b>Viscosity:</b>	100 – 103 (Krebs Units)
<b>Specular Gloss:</b>	3 – 5% @ 85 degrees
<b>Recommended Film Thickness:</b>	Wet – 4.0 to 4.6 mils Dry – 1.5 to 1.7 mils
<b>VOC – VOS Statement:</b>	This product contains less than 50 grams per liter.
<b>Cautions:</b>	<p><b>CAUTION!</b> Do not take internally. Close container after each use.</p> <p><b>KEEP OUT OF REACH OF CHILDREN. KEEP FROM FREEZING.</b></p>

09/22/15

