



**GLASSX
EGGSHELL
2851 LINE**

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
Acrylic/ PVB	Eggshell	Up to 400 Sq Ft Per Gallon	Brush, Roller, Pad or Airless Spray	Clean Water	Warm Soapy Water	30 Minutes	4 Hours	30 Days
PRODUCT NAME: 2851 LINE GLASSX EGGSHELL		A top grade premium paint that combines exceptional performance with eco-friendly manufacturing. Made from recycled polyvinyl butyral resin. An ultra-smooth, ultra-white premium paint that is 50% pre-consumer upcycled paint that is 100% recyclable.						
WHERE TO USE:		Drywall Plaster Wood Metal Masonry	This eggshell latex wall paint Ideal for living rooms, bedrooms, home offices and more. Use on properly prepared plaster, drywall, wood, masonry, plywood and properly primed metal.					
SURFACE PREPARATION:		<p>New Work: The surface to be coated must be clean and free of dust, grease, wax, rust, oil, and bleeding stains.</p> <p>Priming: Drywall – #50 Acrylic Primer Sealer or 5790. Plaster – For best results use No. 50 Acrylic Primer Sealer or 5790. Wood – Alkyd Primer Undercoat Ferrous Metal – Rust inhibiting metal primer Non-Ferrous Metal – PermaBond #100-10. Galvanized – Acrylic Primer Masonry – Use Primer Sealer. To fill porous block use Latex Block Filler 529-11</p> <p>Repaint Work: On previously painted surfaces in good repair, no priming is generally necessary. On glossy surfaces, remove the sheen with sandpaper or steel wool. Patch holes or cracks with appropriate filler. Spot prime bare areas with indicated primer. Remove any oil, chalk, dirt, wax or dust prior to re-coating. Any loose or flaking paint should be removed and the edges feather sanded to produce a smooth, uniform surface.</p>						
APPLICATION:		<p>Stir product with a circular, lifting motion to disperse into a homogenous liquid. To achieve proper results a quality 3/8" nap roller cover is required when using products containing ceramic microspheres.</p> <p>Brush – Nylon or polyester filament.</p> <p>Airless Spray – Tip at atomization pressures will vary with type of equipment, viscosity and temperature. An orifice of .017 - .019 will provide the most satisfactory spray pattern.</p> <p>Best results are more likely obtained by using quality application tools. Do not apply directly over chalky surfaces or bleeding stains.</p>						
NOTE: Formulated without mercury or lead.								

RESIN:	Acrylic/PVB
SOLIDS:	Volume – 35.0
WEIGHT PER GALLON:	10.26 lbs.
VISCOSITY:	96 – 100 (Krebs Units)
SPECULAR GLOSS:	6 – 10% @ 60 degrees
RECOMMENDED FILM THICKNESS:	Wet – 3.5 to 5.0 mils Dry – 1.20 to 1.35 mils
VOC – VOS STATEMENT:	This product contains less than 50 grams of VOC/VOS per liter of coating (.42 lbs per gallon)
CAUTIONS:	<p>CAUTION! Do not take internally. Close container after each use.</p> <p>KEEP OUT OF REACH OF CHILDREN.</p> <p>KEEP FROM FREEZING.</p>

REV 10/24

