



**Acrylic Multi Surface  
Semi-Gloss Finish  
2607 Series**

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
100% Acrylic	SemiGloss	Up to 350 Sq Ft Per Gallon	Airless Spray	Clean Water	Warm Soapy Water	30 Minutes	2 Hours	30 Days
<b>PRODUCT NAME:</b> Acrylic Multi-Surface 2607 Series		Acrylic Multi-Surface Finish is a highly adhesive acrylic coating designed to provide greater bond strength than traditional latex dry fall products that are commonly used on ceilings and upper walls in production and warehouse facilities. Acrylic MultiSurface can be applied directly to aged alkyd coatings, bare masonry, aluminum and galvanized metal surfaces without a primer. The product's superior adhesion and selfpriming characteristics save money by allowing the use of one product to coat a wide variety of surfaces. Acrylic Multi-Surface can often be applied directly over diesel dust and staining from light industrial fumes without cleaning or priming. Because the makeup of contaminants on commercial and industrial ceilings varies widely we recommend applying a sample to insure acceptable results.						
<b>WHERE TO USE:</b>		This product can be used in interior and exterior applications. Recommended for commercial and industrial deck and joist ceilings, bare masonry, galvanized, aluminum and primed or previously painted drywall and ferrous metal surfaces.						
<b>Surface Preparation:</b>		<p><b>New Work:</b> The surface to be coated must be clean and free of oil, grease and other contaminants that could interfere with adhesion. Self-priming on concrete, galvanized and aluminum. Bare concrete block should be filled with 529-11 Latex Block Filler, prime drywall with 4190 Pro Prime Drywall Primer, Prime bare ferrous metal with 1220-111 Alkyd Metal Primer.</p> <p><b>Repaint Work:</b> The surface to be coated must be free of <b>excessive</b> oil, grease or other contaminants that could interfere with adhesion. Test samples are highly recommended on repaint work to confirm proper adhesion and stain blocking.</p>						
<b>Application:</b>		<p>Stir product thoroughly with a circular, lifting motion to disperse into a homogenous liquid. This product is typically applied by airless spray on ceiling deck surfaces, it may be applied to block or drywall surfaces by spray or by spray &amp; back-roll.</p> <p>Spray – Tip size at atomization pressure will vary with type of equipment, viscosity and temperature; an orifice of .017 - .019 will provide the most satisfactory spray pattern.</p> <p>Best results are more likely obtained by using quality application tools. Apply only when surface and air temperatures are above 50°F.</p>						
<b>NOTE: Formulated without mercury or lead.</b>								

<b>Resin Type:</b>	100% Acrylic
<b>Solids:</b>	Weight - 51.5% Volume - 38%
<b>Weight Per Gallon:</b>	10.69 lbs.
<b>Viscosity:</b>	95 – 98 (Krebs Units)
<b>Specular Gloss:</b>	30 - 40% @ 60 degrees
<b>Recommended Film Thickness:</b>	Wet – 4.6 mils Dry – 1.75 mils
<b>VOC / VOS Statement:</b>	This product contains less than 0.83 lbs. or 100 GPL per gallon.
<b>Cautions:</b>	<p style="text-align: center;"><b>CAUTION!</b></p> <p style="text-align: center;">Do not take internally. Close container after each use.</p> <p style="text-align: center;"><b>KEEP OUT OF REACH OF CHILDREN.</b></p> <p><b>WARNING!</b> If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS A BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start find out how to protect yourself and your family by contacting the National Lead Information Hotline 1-800-424-LEAD or log on to <a href="http://www.epa.gov/lead">www.epa.gov/lead</a>.</p>