



<b>Resin Type:</b>	Modified Soyd Alkyd
<b>Solids:</b>	Weight – 76.1% Volume – 54.5%
<b>Weight Per Gallon:</b>	12.44 lbs.
<b>Viscosity:</b>	80 – 85 (Krebs Units)
<b>Specular Gloss:</b>	2 – 3% @ 60 Degrees
<b>Recommended Film Thickness:</b>	Wet – 3.5 to 4.0 mils Dry – 1.7 to 2.0 mils
<b>VOC – VOS Statement:</b>	This product contains less than 2.9 lbs or 350 GPL per gallon.
<b>Cautions:</b>	<p style="text-align: center;"><b>CAUTION! COMBUSTIBLE !</b> <b>Contains Petroleum Distillates</b></p> <p>Keep away from heat &amp; flame. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C) or equivalent) or leave the area. Close container after each use. Avoid contact with skin. Use with adequate ventilation. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.</p> <p style="text-align: center;"><b>KEEP OUT OF REACH OF CHILDREN</b></p>

