O'LEARY PAINT

INTERIOR EXTERIOR

DURAMAX

100% ACRYLIC ENAMEL

GREAT PAINT GREAT PEOPLE

olearypaint.com

DURAMAX

DURAMAX is a premium waterborne acrylic enamel designed for easy application and lasting protection. Streamline on-site maintenance projects with an all-purpose enamel that can be used on interior and exterior trim, doors, handrails, cabinets, or even as a high-performance acrylic wall coating. Drying to an alkyd-like hardness, this low-odor acrylic enamel provides stain and impact resistance that lasts. The 100% acrylic resin creates a durable and flexible coating for long-lasting color protection.

DURAMAX is designed for ease of use and is applicable to all residential, commercial, and light industrial projects. This all-purpose, non-yellowing finish can be applied to walls, equipment, machinery, piping, structural steel, storage tanks, wood or metal trim, railings, pre-finished siding, furniture, windows, doors, cabinets, and shelving.

FEATURES

- 100% Acrylic Waterborne Formula
- Easy Application
- Excellent Color and Gloss Retention
- Low-Odor and Water Clean-up

BENEFITS

100% Acrylic Formula

The durable 100% acrylic resin provides fantastic color and gloss retention. Will not crack, chip, yellow, or chalk when applied to exterior surfaces.

Easy Application

Waterborne formulation offers an easy-to-apply product with good brush and roll qualities and convenient soap and water cleanup.

All-Purpose Enamel

Can be applied to a variety of surfaces including doors, trim, and equipment. Can also be used as a high-performance acrylic for commercial applications.

TECHNICAL INFORMATION

BASES: SATIN - 9200 SERIES · SEMI-GLOSS - 9000 SERIES · GLOSS - 8000 SERIES

APPLICATION INFORMATION

Drying Time at 77° F 50% R.H:

To Touch: 30 Minutes*

Recoat: 4 Hours*

* Cooler temperatures and higher relative humidity will extend dry times

Recommended Spreading Rate:

400 sq. ft./gal to achieve
3.0 - 4.0 mils WFT; 1.0 - 1.5 mils DFT

Solids Content:

Volume: 37% ± 2

EQUIPMENT RECOMMENDATIONS

Airless: Minimum .70 GPM, 2500 PSI, .017-.019" tip.

HVLP: Twin-stage turbine, 5-8 PSI, .051 to .070 projector set

Roller: Short nap woven cover

Brush: 100% Nylon or Synthetic Blend

SAFETY AND COMPLIANCE

VOC Content:

< 240 g/L 2.0 lbs./Gal

PRIMING RECOMMENDATIONS

Drywall: High Hiding Drywall Primer/Sealer, 1200.

Plaster/Masonry: Concrete Sealer, 5090.

Wood: Wall and Trim Primer, 1330.

Galvanized Surfaces: Sungard Bonding Primer, 2090.

Steel Surfaces: Nexbond, IS113.

Block: Latex Block Filler, 529-11.

Repaint: Self-priming with appropriate surface prep. May be applied over existing coatings only after sample applications have been made to check the sensitivity of the existing coating.