



GRIPCRETE HP
ACRYLIC MASONRY
HI-BUILD
7168.10

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
Acrylic	Flat	90-100 Sq Ft Per Gallon	Brush, Roller or Airless Spray	Clean Water	Warm Soapy Water	1-2 Hours	Overnight	14 Days
PRODUCT NAME: 7168.10 GRIPCRETE HP ACRYLIC MASONRY HI-BUILD		GRIPCRETE HP ACRYLIC MASONRY HI-BUILD is a 100% acrylic exterior high-build coating designed to provide lasting protection and increased application efficiencies. This flexible coating is formulated for weather-proofing masonry surfaces to protect against wind-driven rain. Exceptional resistance to alkali, efflorescence, and dirt pick-up extends the coatings lifecycle and reduces ongoing maintenance. Tolerating a pH of 7-13 allows application directly to fresh concrete without the use of specialty primers helping reduce labor and material costs.						
WHERE TO USE:		GRIPCRETE HP ACRYLIC MASONRY HI-BUILD is designed for professional application and can be applied to a variety of vertical cementitious surfaces providing both beauty and protection. This product is specifically formulated for tilt-up, poured in place concrete, CMU, split-face, EIFS, stucco and other masonry surfaces requiring protection from the harshest elements.						
SURFACE PREPARATION:		Allow substrates to dry inside out. Surfaces must be clean and free of dirt or any other contaminates that would prevent proper adhesion or penetration. Mortar joints must be raked clean of any loose material before finishing. New masonry surfaces should be allowed to cure for at least 7 days before applying surfacer. Fill significant voids/defects with the appropriate exterior patching material.						
APPLICATION:		Mix thoroughly before use. Apply by brush, roller, or airless spray or conventional spray. If sprayed, product should be back-rolled or brushed to properly work into surface. Apply when the ambient, surface, and material temperatures 50° F or higher. DO NOT APPLY IN DIRECT SUNLIGHT. Thinning is not recommended. All products are formulated ready for application. If needed, thin sparingly and do not exceed 2oz per gallon. Clean all applicators with water immediately after use.						
NOTE: Formulated without mercury or lead.								

RESIN:	100% Acrylic
SOLIDS:	Weight – 62% Volume – 47%
WEIGHT PER GALLON:	11.7 lbs.
VISCOSITY:	110 (Krebs Units)
FLASH POINT:	200°F or over (TT-P-141, Method 4293)
SPECULAR GLOSS:	2 – 6% @ 60 Degrees
SAG RATING:	60+/60+
RECOMMENDED FILM THICKNESS:	Dry - 6.4 - 8.3 mils
LIGHT REFLECTANCE:	N / A
VOC – VOS STATEMENT:	This product contains 50 grams per liter.
CAUTIONS:	<p style="text-align: center;">CAUTION! Do not take internally. Close container after each use. KEEP FROM FREEZING. KEEP OUT OF REACH OF CHILDREN.</p>

Revised 03/2025

