



**GRIPCRETE
VERTICAL CONCRETE
STAIN
7167.10**

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
Acrylic	Flat	150-250 Sq Ft Per Gallon	Spray	Clean Water	Warm Soapy Water	30-60 Minutes	30-60 Minutes	7 Days
PRODUCT NAME: 7167.10 GRIPCRETE VERTICAL CONCRETE STAIN		GRIPCRETE VERTICAL CONCRETE STAIN is a 100% acrylic concrete stain designed for easy application while improving aesthetics of exterior vertical concrete surfaces. Specifically formulated as a water-repellent coating, the opaque finish has high alkali and efflorescence resistance. Reduce labor and material costs by eliminating specialty primers with this self-priming, pH-tolerant (7-13) coating. This self-priming finish will increase efficiencies by providing a finished system in as little as two coats versus traditional three coat systems.						
WHERE TO USE:		GRIPCRETE VERTICAL CONCRETE STAIN is designed specifically for vertical, non-porous cementitious surfaces where alkali and efflorescence resistance is required. This product is best used on new and unsealed tilt-up, precast, poured concrete, CMU, and stucco surfaces.						
SURFACE PREPARATION:		Surfaces must be dry, clean and free of dust, dirt, grease, oil or any other contaminants that may prevent proper adhesion. All loose paint must be removed and glossy surfaces dulled by sanding. Plaster surfaces must be well cured, and porous masonry surfaces should be filled with block filler. Tape joints and nailheads on drywall should be sanded and dusted clean before finishing. Mud on joints and nailheads must be thoroughly cured before finishing to help avoid photographing. Galvanized surfaces shall have all oils removed prior to application of coating.						
APPLICATION:		Mix thoroughly before use. Apply by brush, roller, or airless spray or conventional spray. If sprayed, product should be back-rolled or brushed to properly work into surface. Apply when the ambient, surface, and material temperatures 50° F or higher. DO NOT APPLY IN DIRECT SUNLIGHT. Thinning is not recommended. Clean all applicators with water immediately after use						
NOTE: Formulated without mercury or lead.								

RESIN:	100% Acrylic
SOLIDS:	Weight – 46% Volume – 30%
WEIGHT PER GALLON:	10.7 lbs.
VISCOSITY:	73 (Krebs Units)
FLASH POINT:	200°F or over (TT-P-141, Method 4293)
SPECULAR GLOSS:	2 – 6% @ 60 Degrees
SAG RATING:	<14/25
RECOMMENDED FILM THICKNESS:	N / A
LIGHT REFLECTANCE:	N / A
VOC – VOS STATEMENT:	This product contains 50 grams per liter.
CAUTIONS:	<p>CAUTION! Do not take internally. Close container after each use.</p> <p>KEEP FROM FREEZING.</p> <p>KEEP OUT OF REACH OF CHILDREN.</p>

Revised 03/2025

