



**O'LEARY  
PAINT**

PREMIUM

**INTERIOR**

**GRIPCRETE**  
BLOCK FILLER



**GREAT PAINT GREAT PEOPLE**

# BLOCK FILLER

GRIPCRETE BLOCK FILLER is a general-purpose interior block filler designed to fill and smooth interior masonry surfaces. When applied properly, it will produce a paintable surface with reduced pin-holes to improve application and performance of subsequent finishes. The zero-VOC, LEED V4 compliant formulation meets the strictest air quality standards.

GRIPCRETE BLOCK FILLER is formulated for professional spray application to bare, unpainted masonry surfaces. The filling and sealing qualities makes it ideal for preparing masonry surfaces in commercial, institutional, and light industrial construction. Can be finished with professional latex finishes and waterborne pre-catalyzed epoxies.

## FEATURES

- Excellent Fill & Sealing Properties
- High-Hiding Formula
- LEED v4 Credit Eligible

## BENEFITS

### Labor and Material Savings

Improved filling and sealing properties fills pores with fewer pin-holes reducing the amount of time and topcoat required to finish surfaces

### Environmentally Responsible Coating

Low-odor, zero-VOC formula minimizes impact on other trades during application while meeting the strictest air quality standards.



## TECHNICAL INFORMATION

### APPLICATION INFORMATION

Drying Time at 77° F 50% R.H:

To Touch: 1 Hour\*

Recoat: Overnight\*

\* Cooler temperatures and higher relative humidity will extend dry times

Recommended Spreading Rate:

80-100 sq. ft. / Gal to achieve 16-20 mils WFT; 8.5-10.5 mils DFT

Solids Content:

Volume: 48% ± 2 Weight: 69% ± 2

### BASES: WHITE - 529-11 SERIES

### EQUIPMENT RECOMMENDATIONS

Roller: 3/4"- 1 1/4" nap shed-resistant or lambswool cover

Brush: 100% nylon or synthetic blend

Airless: Minimum 1 GPM with .021" tip @2300-2700 PSI

### SAFETY AND COMPLIANCE

VOC Content:

<5 g/L 0.02 lbs./Gal

### FINISHING RECOMMENDATIONS

**High-Performance Acrylic:** AMS MULTI-SURFACE ACRYLIC AND DURACAT EPOXY.

**Premium Finish:** CERAMIC COAT and VINTAGE 30 Series

**Professional Finish:** PRO HIDE and NUCON Series

### Exterior Use:

May be used on exterior surfaces but must be topcoated within 30 days. Ask for details.