




O'LEARY
PAINT

INTERIOR

PRO HIDE
INTERIOR LATEX WALL FINISH



GREAT PAINT GREAT PEOPLE

olearypaint.com

PRO HIDE

PRO HIDE is a professional line of interior latex finishes designed for reliable, everyday performance. High-hiding and low-spatter features provide easier application for faster coverage, improved productivity, and faster job turnaround. LEED Green Building Rating GS-11 compliant formulation delivers easy production application with outstanding touch-up ideal for commercial and institutional projects meeting the strictest air quality standards.

PRO HIDE is designed to deliver easy and consistent results for the professional painter. The durable finish can be applied to drywall, plaster, wallboard, and other prepared surfaces. It is ideally suited for maintenance and new construction painting for commercial, institutional, and residential projects. May also be applied in light industrial facilities in non-corrosive areas.

FEATURES

- LEED GS-11 Compliant
- Easy Application
- Cost & Labor Savings
- Professional Interior Finish

BENEFITS

Production Driven Performance



High-hiding, sag and spatter resistant formula delivers quicker coverage for reduced labor and material costs.

Versatile Application

Easy brush, roll, and spray application with outstanding durability and touch-up provide value to professional painters during application and maintenance technicians for ongoing upkeep.

Environmentally Responsible Finish

LEED Green Building Rating GS-11 compliant finish meets the performance needs of contractors, specifiers, property managers, and general contractors looking to meet the strictest air quality standards.



LOW-SPATTER APPLICATION

TECHNICAL INFORMATION

APPLICATION INFORMATION

Drying Time at 77° F 50% R.H.:

To Touch: 1 Hours* Recoat: 4 hours*

*Cooler temperatures and higher relative humidity will extend dry times

Recommended Spreading Rate:

400 sq. ft. /Gal to achieve
3.5-4.5 mils WFT; 1.2-1.6 mils DFT

Solids Content:

Volume: 37% ± 2 Weight: 58% ± 2

BASES: FLAT - 7100 SERIES • LO-SHEEN - 7400 SERIES • EGGSEHELL - 7200 SERIES • SATIN - 5800 SERIES • SEMI-GLOSS - 7300 SERIES

EQUIPMENT RECOMMENDATIONS

Airless: Minimum .70 GPM, 2500 PSI, .017-.019" Tip

HVLP: Twin-stage turbine, 5-8 PSI, .051 to .070 projector set

Roller: 3/8" - 1/2" nap synthetic cover

Brush: 100% Nylon or Synthetic Blend

SAFETY AND COMPLIANCE

VOC Content:

< 50 g/L 0.42 lbs./Gal

PRIMER RECOMMENDATIONS

New Work

Drywall: High Hide Primer/Sealer, 4190.

Plaster/Masonry: Masonry Sealer, 5090.

Wood: 50 Block-It Acrylic Primer Sealer.

Galvanized Surfaces: Self Priming, 50 Block-It.

Steel Surfaces: 2090 Bonding Primer.

Block: 529-11 Block Filler.

Repaint: Self-Priming with appropriate surface preparation.