



**O'LEARY
PAINT**

**INTERIOR
EXTERIOR**

BLOCK-IT #50
ACRYLIC STAIN KILLING PRIMER



GREAT PAINT GREAT PEOPLE

olearypaint.com

BLOCK-IT

BLOCK-IT is a premium acrylic stain blocking primer designed to block and seal typical household and commercial stains. This high hiding, fast drying, low odor primer sealer that is easy to apply to both new and old interior and exterior surfaces. Resists burning from hot or green plaster, it lays the nap well on paper surfaced drywall construction. Its fast dry and recoat times make it possible to apply two coats in one day. Provides an excellent foundation for all paints, seals stains of various types: asphalt, smoke, light water stains, and wood stains (except redwood and cedar). Adheres to glossy surfaces without sanding.

On drywall construction, over joint cement, interior plaster, wood, brick, concrete, building blocks, masonite and asphalt impregnated surfaces. It is an excellent first coat sealer on asphalt impregnated pipe insulation. May also be used as an undercoat over flat surfaces where it is desired to apply a coat of alkyd or oil base enamel without danger to gloss strike in. May be applied directly to enameled, varnished, and galvanized surfaces. Ideal for exterior masonry surfaces. Not recommended for exterior wood surfaces.

FEATURES

- Tough 100% Acrylic Formula
- Excellent Adhesion
- Interior and Exterior Use
- Low Odor and Low-VOC

BENEFITS

100% Acrylic Resin

Premium resin provides exceptional adhesion for both interior and exterior projects.

Tough Stain Blocker

Tougher than ordinary universal primers, BLOCK-IT simply blocks stains better. Blocks marker, crayon, lipstick, graffiti, water stains and much, much more.

Fast Drying

With a dry time of under an hour, you can prime and paint in the same day helping jobs get done more efficiently.



TECHNICAL INFORMATION

APPLICATION INFORMATION

Drying Time at 77° F 50% R.H:

To Touch: 1 hour*

Recoat: 1 hour*

* Cooler temperatures and higher relative humidity will extend dry times

Recommended Spreading Rate:

400 sq. ft./gal to achieve
3.5-4.0 mils WFT; 1.0-1.2 mils DFT

Solids Content:

Volume: 39% ± 2 Weight: 52% ± 2

BASES: WHITE - 50 SERIES | DEEP BASE - 55 SERIES

EQUIPMENT RECOMMENDATIONS

Roller: ½" – ¾" nap shed-resistant cover or lambswool cover

Brush: 100% nylon or synthetic blend

Airless: Minimum ½ GPM, .017" tip @ 2300-2700 PSI

HVLP: Twin-stage turbine, 5 – 8 PSI, .051 to .070 projector set

SAFETY AND COMPLIANCE

VOC Content:

< 200 g/L 1.67 lbs./Gal

FINISHING RECOMMENDATIONS

Interior

Can be finished with any O'Leary interior latex or acrylic finishes.

Exterior

Can be finished with any O'Leary exterior paint finishes.

Compatibility

BLOCK-IT #50 can be top-coated with a wide range of interior and exterior latex and acrylic coatings. Perform a small test area to confirm compatibility prior starting any painting project.