



SUNGARD
Exterior Acrylic
Low Luster
5551

Type	Sheen	Spread Rate	Recommended Application	Thinner	Clean Up	DRY TIME		
						Tack Free	Re-coat	Cure
100% Acrylic	Low Luster	Up to 400 Sq Ft Per Gallon	Brush, Roller, Pad or Spray	Clean Water	Warm Soapy Water	60 Minutes	4 Hours	10-14 Days
PRODUCT NAME: 5551 LINE Sungard Exterior Acrylic Low Luster		A 100% Acrylic Low Luster House Paint which provides lasting service over new or previously painted surfaces in good condition. Sungard Acrylic House Paint will provide a durable and protective finish on any properly prepared and primed exterior surface. recommended for use on aluminum, vinyl, and wood siding, clapboard, shakes, shingles, plywood, masonry, and primed metal down to surface and air temperature of 35 F°.						
WHERE TO USE:		On exterior siding, foundations, facia, shutters or retaining walls.						
Surface Preparation:		Surface to be painted must be clean and free of dirt, chalk, wax, grease, rust or loose, flaking paint. Dirt and chalk should be removed by power washing or hand scrubbing with an abrasive cleanser and water, followed by a clean water rinse. Rust must be removed by blasting, sanding or by conscientious power tool cleaning. Remove loose paint by scraping. Feather sand rough edges to insure a smooth finish coat. Glossy surfaces must be dulled by lightly sanding. Remove sanding dust before paint application. Any exposed substrate should be spot primed with the appropriate primer. Priming – (New or Bare Surfaces) WOOD – Use O’Leary, 2090 Exterior Acrylic Bonding Primer MASONRY – Use O’Leary, 5090 Pro Primer Barrier Coat. To fill porous block, use O’Leary 529-11 Pro Prime Block Filler FERROUS METAL – Rust Inhibiting Metal Primer NON-FERROUS METAL – Use O’Leary 50 Block It WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.						
Application:		Stir product with a circular, lifting motion before you begin to paint. Acrylic Latex Flat House Paint may be applied by brush, spray, pad or roller, at a rate of application not to exceed 400 sq ft per gallon. Surface texture and porosity will affect actual yield. For best brush application results, use a quality synthetic filament brush. For roller application, use a 3/8” or 1/2” nap cover for smooth surfaces, a 3/4” nap cover for semi-rough surfaces and a 1” or 1-1/4” nap cover for rough surfaces. For spray application, thin with clean water, up to 10% reduction if necessary. Do not apply to hot surfaces or in direct sunlight. Do not apply if rain is threatening.						
NOTE: Formulated without mercury or lead.								

Resin Type:	100% Acrylic
Solids:	Volume – 37%
Weight Per Gallon:	10.51 lbs.
Viscosity:	95 – 100 (Krebs Units)
Specular Gloss:	10 - 15% @ 60 Degrees
Recommended Film Thickness:	Wet – 4.0 to 5.35 mils Dry – 1.48 to 1.98 mils
VOC – VOS Statement:	This product contains less than 1.05 lbs or 125 GPL per gallon.
CAUTIONS:	CAUTION ! Do not take internally. Close container after each use. KEEP OUT OF REACH OF CHILDREN !

Rev. 01/19/2023

